

**Barcode Scanner****Model: RT670B Technical Specifications****posDiGi**

<b>Reading Distance</b>	<b>4mil</b>	<b>5-60mm</b>
	<b>5mil</b>	<b>8-100mm</b>
	<b>10mil</b>	<b>15-250mm</b>
	<b>35mil</b>	<b>150-500mm</b>
	<b>43mil</b>	<b>150-800mm</b>
<b>Barcode Width(Max)</b>	<b>300mm</b>	
<b>Light Source Type</b>	<b>650nm visible laser</b>	
<b>Scan Mode</b>	<b>Single-line laser</b>	
<b>Scan Speed</b>	<b>100 times / sec.</b>	
<b>Scan Accuracy</b>	<b>4mil(PCS0.9)</b>	
<b>Scan Angel</b>	<b>Narrow 32°</b>	<b>Elevation 68°</b>
<b>Decoding Capability</b>	<b>Universal one-dimensional barcode:EAN-8 , EAN-13 , UPC-A,Code39,Code93,Code128,EAN128,Codaber, IN 2of5,Ma 2of5,msi and so on</b>	
<b>Interface</b>	<b>USB,PS2 , RS232</b>	
<b>Scan Method</b>	<b>Manual/Automatic/self-induced (self-induced another model)</b>	
<b>Tips Method</b>	<b>Buzzer, Light</b>	
<b>Print Contrast</b>	<b>30% minimum reflectance difference</b>	
<b>Environmental Brightness</b>	<b>In direct sunlight normal scanning</b>	
<b>Error Rate</b>	<b>1/6million</b>	
<b>Operating Temperature</b>	<b>0°C to 40°C</b>	
<b>Storage Temperature</b>	<b>-20°C to A2260°C</b>	
<b>Relative Humidity</b>	<b>5% to 95% non-condensing</b>	
<b>Seismic Performance</b>	<b>Normal use after 2M multiple drops</b>	
<b>Material Parameters</b>		
<b>Processor</b>	<b>8</b>	
<b>Optical Devices</b>	<b>Gilding</b>	
<b>Physical Parameters</b>		
<b>Operation Voltage</b>	<b>5V DC</b>	
<b>Current Consumption</b>	<b>Static 35MmA, Instant 85mA</b>	
<b>Scanner Dimension</b>	<b>L×W×H : 7cm×4cm×16cm</b>	
<b>Weight</b>	<b>About 250g</b>	
<b>Standard Cable Length</b>	<b>2M</b>	